

Diesel Ute Pack Tanks

100 – 800 LTRS - Essential 12V



	DMP100E	DMP200E	DMP400E	DMP600E	DMP800E
Manufacturer	Polymaster Pty Ltd	Polymaster Pty Ltd	Polymaster Pty Ltd	Polymaster Pty Ltd	Polymaster Pty Ltd
Tank Type	Ute Pack	Ute Pack	Ute Pack	Ute Pack	Ute Pack
Nominal Capacity (ltrs)	100	200	400	600	800
Working Volume (ltrs)	100	200	400	600	800
Tare Weight (kg)	22	33	52	62	82
Tank Material of Construction	Polyethylene - 7040	Polyethylene – 7040	Polyethylene – 7040	Polyethylene – 7040	Polyethylene - 7040
Lid Material of Construction	Polyethylene - 7050	Polyethylene – 7050	Polyethylene – 7050	Polyethylene – 7050	Polyethylene - 7050
Overall Length (mm)	770	1050	1680	1720	1720
Overall Width (mm)	540	750	750	890	890
Overall Height (mm)	500	600	600	755	925
Max. Specific Gravity Rating	1	1	1	1	1
Colour	Light Grey / Caster Red	Light Grey / Caster Red	Light Grey / Caster Red	Light Grey / Caster Red	Light Grey / Caster Red
Worksafe Approval	Packaging Group 3	Packaging Group 3	Packaging Group 3	Packaging Group 3	Packaging Group 3
UN Specification	Transport of Dangerous goods	Transport of Dangerous goods	Transport of Dangerous goods	Transport of Dangerous goods	Transport of Dangerous goods
Standard Fitting Specifications					
Fill Connection					
Size	DN50 F BSP	DN50 F BSP	DN50 F BSP	DN50 F BSP	DN50 F BSP
MOC/Type	Galvanised Fill Plate	Galvanised Fill Plate	Galvanised Fill Plate	Galvanised Fill Plate	Galvanised Fill Plate
Max Fill Rate (L/min)	N/A	N/A	N/A	N/A	N/A
Fill Plate Cap	DN50 M BSP	DN50 M BSP	DN50 M BSP	DN50 M BSP	DN50 M BSP
MOC/Type	Polyamide w/ Vent	Polyamide w/ Vent	Polyamide w/ Vent	Polyamide w/ Vent	Polyamide w/ Vent

The information provided in this document is general in nature and does not take into account your personal situation. You should consider whether the information is appropriate to your needs, and where appropriate, seek professional advice. Although every effort has been made to verify the accuracy of the information contained in this document, Polymaster, its officers, employees, and agents disclaim all liability (except for liability which by law cannot be excluded), for any error, inaccuracy in, or omission from the information contained in this document or any loss or damage suffered by any person directly or indirectly through relying on this information.

Pump					
Make	Piusi	Piusi	Piusi	Piusi	Piusi
Model	F00342000	F00342000	F00342000	F00342000	F00342000
Phase	DC	DC	DC	DC	DC
Voltage (V)	12	12	12	12	12
Flow Rate (L/min)	50	50	50	50	50
IP Rating	IP55	IP55	IP55	IP55	IP55
Outlet					
Size	DN20	DN20	DN20	DN20	DN20
Type	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle
Volume (L/min)	65	65	65	65	65
Hose					
Length (Meters)	4	4	4	4	4
Size	DN20	DN20	DN20	DN20	DN20
MOC	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade
Static Lead					
Length (Meters)	2	2	2	2	2
Connection	Alligator Clip	Alligator Clip	Alligator Clip	Alligator Clip	Alligator Clip
Static Lead Must be Connected for Safe Operation and Compliance with Worksafe Approval.					

Optional Fitting Specifications
--

In-Line Wire Strainer	
Size	DN20
MOC	Brass
Particle Size (Microns)	350

Diesel Fuel Gauge (All Models)	
Type	Empty thru. Full

The information provided in this document is general in nature and does not take into account your personal situation. You should consider whether the information is appropriate to your needs, and where appropriate, seek professional advice. Although every effort has been made to verify the accuracy of the information contained in this document, Polymaster, its officers, employees, and agents disclaim all liability (except for liability which by law cannot be excluded), for any error, inaccuracy in, or omission from the information contained in this document or any loss or damage suffered by any person directly or indirectly through relying on this information.

